

EXTRAFLEX EXPOFLEX CORRFLEX



Stainless Steel Flexible Flue Lining Solution

(AVAILABLE IN ALL LENGTHS. ROLLS TILL 100 m)

Designations

Product marking according to the European standard: EN 1856-2.

EXTRAFLEX (Multifuel)
 With seals T200 P1 W V2 L70010 O dn 50÷160
 T200 P1 W V2 L70012 O dn 50÷160
 Without seals T600 N1 W V2 L70010 G dn 50÷400
 T600 N1 W V2 L70012 G dn 50÷400

EXPOFLEX (Wood)
 With seals T200 P1 W V2 L50010 O dn 50÷160
 T200 P1 W V2 L50012 O dn 50÷160
 Without seals T600 N1 W V2 L50010 G dn 50÷400
 T600 N1 W V2 L50012 G dn 50÷400

CORRFLEX (Gas & Kerosene)
 With seals T200 P1 D V2 L50010 O dn 50÷160
 T200 P1 D V2 L50012 O dn 50÷160
 Without seals T600 N1 D V2 L50010 G dn 50÷400
 T600 N1 D V2 L50012 G dn 50÷400

Available diameters - mm

.....
 60 - 80 - 100 - 130 - 150 - 180 - 200 - 220 - 250 -
 300 - 350
 (dn 300, 350 on request)

EXPOFLEX TWIN LAYERS SYSTEMS

APPLICATION:

Twin skin flexible chimney liner designed for gas, oil and multifuel, where the maximum flue gas temperature does not exceed 600 °C.

- EXTRAFLEX: inner and outer skins in 904L grade stainless steel
- EXPOFLEX: inner and outer skins in 316L grade stainless steel
- 0.10 mm thickness (available in 0.12 mm)
- V2 Corrosion resistance
- Class 1 applications
- Suitable for multifuel, biomass, pellet, wood, standard oil and gas appliances
- Compatible with EXPO screw fit component
- Compatible with all EXPO Products
- Install in direction arrow indicated on liner
- CE certified - European Marking: EN 1856-2
- HETAS approved
- UK manufactured
- LIFETIME GUARANTEE (according to EXPO's guidelines)

CORRFLEX SINGLE LAYERS SYSTEM

APPLICATION:

Single wall stainless steel flexible flue liner designed for atmospheric gas and kerosene appliances.

- CORRFLEX: single skin in 316L grade
- 0.10 mm thickness (available in 0.12 mm)
- V2 Corrosion resistance
- Suitable for ventilation
- Compatible with EXPO screw fit component
- Compatible with all EXPO Products
- Install in direction arrow indicated on liner
- CE certified - European Marking: EN 1856-2
- UK manufactured
- LIFETIME GUARANTEE (according to EXPO's guidelines)

EXTRAFLEX

Stainless Steel Flexible Flue Lining Solution



904DP...

Twin wall smooth inner surface flexible liner in stainless steel AISI 904L.



PLAST IMB05

Available in roll.



DISPENSER IMB10

Available in dispenser.

Ø	CODE	£/M
60	12904DP06	
80	12904DP08	
100	12904DP10	
125	12904DP125	
150	12904DP15	
180	12904DP18	
200	12904DP20	
220	12904DP22	
250	12904DP25	
300	12904DP30	
350	12904DP30	

Ø	CODE	£	m	L	H
60	12904DP06	30	57	86	
80	12904DP08	30	66	100	
100	12904DP10	30	90	63	
125	12904DP125	30	120	63	
150	12904DP15	30	120	104	
180	12904DP18	30	120	120	
200	12904DP20	25	165	85	
220	12904DP22	25	160	85	
250	12904DP25	20	165	82	
300	12904DP30	5	-	-	

Ø	CODE	£	m	L	H
60	1290460DPB1006	60	80	80	
80	1290460DPB1008	60	80	80	
100	1290460DPB1010	60	80	80	
125	1290450DPB10125	50	80	120	
150	1290435DPB1015	35	120	120	
180	1290430DPB1018	30	120	120	
200	1290430DPB1020	30	120	140	
200	1290420DPB1020	20	120	140	