

EXTRAFLEX EXPOFLEX CORRFLEX



Stainless Steel Flexible Flue Lining Solution



EXTRAFLEX, EXPOFLEX TWIN LAYERS SYSTEMS

APPLICATION:

Twin skin flexible chimney liner designed for gas, oil and multifuel, where the maximum flue gas temperature does not exceed 600 °C.

- EXTRAFLEX: inner and outer skins in 904L grade stainless steel
- EXPOFLEX: inner and outer skins in 316L grade stainless steel
- 0.10 mm thickness (available in 0.12 mm)
- V2 Corrosion resistance
- Class 1 applications
- Suitable for multifuel, biomass, pellet, wood, standard oil and gas appliances
- Compatible with EXPO screw fit component
- Compatible with all EXPO Products
- Install in direction arrow indicated on liner
- CE certified - European Marking: EN 1856-2
- HETAS approved
- UK manufactured
- LIFETIME GUARANTEE (according to EXPO's guidelines)

AVAILABLE IN ALL LENGTHS.
ROLLS TILL 100 m

Designations

Product marking according to the European standard: EN 1856-2.

EXTRAFLEX (Multifuel)

With seals	T200 P1 W V2 L70010 O dn 50÷160
	T200 P1 W V2 L70012 O dn 50÷160
Without seals	T600 N1 W V2 L70010 G dn 50÷400
	T600 N1 W V2 L70012 G dn 50÷400

EXPOFLEX (Wood)

With seals	T200 P1 W V2 L50010 O dn 50÷160
	T200 P1 W V2 L50012 O dn 50÷160
Without seals	T600 N1 W V2 L50010 G dn 50÷400
	T600 N1 W V2 L50012 G dn 50÷400

CORRFLEX (Gas & Kerosene)

With seals	T200 P1 D V2 L50010 O dn 50÷160
	T200 P1 D V2 L50012 O dn 50÷160
Without seals	T600 N1 D V2 L50010 G dn 50÷400
	T600 N1 D V2 L50012 G dn 50÷400

CORRFLEX SINGLE LAYERS SYSTEM

APPLICATION:

Single wall stainless steel flexible flue liner designed for atmospheric gas and kerosene appliances.

- CORRFLEX: single skin in 316L grade
- 0.10 mm thickness (available in 0.12 mm)
- V2 Corrosion resistance
- Suitable for ventilation
- Compatible with EXPO screw fit component
- Compatible with all EXPO Products
- Install in direction arrow indicated on liner
- CE certified - European Marking: EN 1856-2
- UK manufactured
- LIFETIME GUARANTEE (according to EXPO's guidelines)

Available diameters - mm

.....
60 - 80 - 100 - 130 - 150 - 180 - 200 - 220 - 250 -
300 - 350
(dn 300, 350 on request)
.....

EXTRAFLEX

Stainless Steel Flexible Flue Lining Solution



904DP...

Twin wall smooth inner surface flexible liner in stainless steel AISI 904L.



PLAST IMB05

Available in roll.



904DP...

Available in dispenser.

Ø	CODE	£/M
60	12904DP06	
80	12904DP08	
100	12904DP10	
125	12904DP10	
150	12904DP10	
180	12904DP10	
200	12904DP10	
220	12904DP10	
250	12904DP10	
300	12904DP10	
350	12904DP10	

Ø	CODE	£/M
60	12904DP06	
80	12904DP08	
100	12904DP10	
125	12904DP10	
150	12904DP10	
180	12904DP10	
200	12904DP10	
220	12904DP10	
250	12904DP10	
300	12904DP10	
350	12904DP10	

Ø	CODE	£/M
60	12904DP06	
80	12904DP08	
100	12904DP10	
125	12904DP10	
150	12904DP10	
180	12904DP10	
200	12904DP10	
220	12904DP10	
250	12904DP10	
300	12904DP10	
350	12904DP10	